

Laserworld PL-20.000RGB IP65

A high-performance full-color laser with integrated multi-control mainboard. **Great DMX / ArtNET control** with internal security settings, which makes it very easy to control several devices together, even in the rest of the DMX network.

Full laser show software license included in the scope of delivery! Perfect for large club installations, indoor events and outdoor events. Perfect for large nightclub installations, indoor events, medium-sized as well as large outdoor events. Works fantastic for large productions, especially when working with effect generators in the console (chaser effects, color effects, etc.).

IP65 waterproof laser system, suitable for outdoor use. Includes waterproof plastic case.

- 20'000 mW guaranteed power
- Graphics capable 35kpps @ 8°
- Max scan angle 50°
- Full colour mixing analog modulation
- Sharp intense beams ca. 6.5 mm beam diameter and low divergence of 0.9 mrad
- **IP65** waterproof housing
- Save safety settings direct to the ShowNET mainboard
- Link multiple units with linking Power, DMX and ILDA
- Free computer control software Showeditor upgradable to Showcontroller
- Multiple control modes Auto, DMX, Artnet and ILDA
- Display for easy selection of operating modes
- Incl. waterproof flightcase

ShowNET mainboard as standard:

• Various control options:



| Guaranteed Power at aperture | 20'000 mW |
|------------------------------|---|
| Power Red | 6'000 mW / 638 nm |
| Power Green | 8'000 mW / 520 nm |
| Power Blue | 8'000 mW / 450 nm |
| Beam Specifications | ca. 6.5 mm / 0.9 mrad |
| Scanner | 35kpps @ 8° |
| Max. Scan Angle | 50° |
| Operation Modes | ILDA, DMX, LAN, ArtNet, ILDA streaming, integrated SD card, stand-alone |
| Laser Class | 4 |
| | |

| Laser Source | Diode |
|-------------------|--|
| IP rating | IP65 |
| Basic Patterns | over 120 (layers, tunnels, fences, waves, etc.) - more updatable by user |
| Accessories | Incl. waterproof flightcase, key, power cable, manual; full version of Showeditor included |
| Power Supply | 85 V - 250 V AC, 50/60 Hz |
| Power Consumption | 750 W |
| Dimensions | 427 x 280 x 220 mm (L x W x H) |
| Weight | 27 kg |
| EAN / MPN | 7640144997922 |
| | |



















AVAILABLE MODIFICATIONS:



^{*}Due to Advanced Optical Correction technology used in our laser systems the optical power of each colour within installed laser module(s) may slightly differ from the specification of respective laser module(s). Divergence FWHM average depending on model.